# FRIGIDAIRE.

# FFPA0822U1



## SIGNATURE FEATURES

# **Multi-Speed Fan**

Features three different fan speeds, for more cooling flexibility.

### **Remote Control**

Allows you to precisely control the temperature and fan speed from across the room.

# Effortless™ Clean Filter

Our antibacterial filter reduces bacteria, room odors and other airborne particles for a healthier, more comfortable environment.

# Programmable 24-Hour On/Off Timer

Customize times to fit your schedule for immediate comfort when you get home. The built-in timer allows you to preset the unit to turn on and off in half-hour increments.

# HOME COMFORT

PORTABLE AIR CONDITIONER

#### **PRODUCT DIMENSIONS**

Height	27-29/32"
Width	18-24/32"
Depth	15-5/32"

#### MORE EASY-TO-USE FEATURES

#### Sleep Mode

Maximum comfort throughout the evening hours with the added benefit of energy savings. With Sleep Mode, the temperature gradually increases a few degrees over the evening.

#### Ready-Select® Controls

Easily select options with the touch of a button.

#### SpaceWise® Portable Design

Wheels allow you to easily move the air conditioner from room to room, providing cool air when and where you need.

#### Effortless™ Restart

Automatically resumes operating at its previous settings when power is restored to your unit.

# Effortless™ Temperature Control

Our air conditioners maintain the preset room temperature, so you will remain comfortable at all times.

PERFORMANCE	BTUs	
Cooling	8,000	
D.O.E.	4,400	



#### PERFORMANCE


ASHRAE BTU (Cool)	8,000
D.O.E. BTU	4,400
Dehumidification (Pints/Hour)	2.8
Cool Area (Up To Sq.Ft.)	350
Energy Efficiency Ratio	11.4
ELECTRICAL	
Volts	115
Amps (Cool)	9.0
Watts (Cool)	877
Length of Power Cord (Min./Max.)	6'/6.5'
Plug Type (NEMA)	LCDI (5-15P)
FEATURES	
Electronic Controls	Ready-Select® Controls
Fan Speeds (Cool/Fan)	3/3
Low Voltage Start-Up	Yes
Energy Save	
Sleep Mode	Yes
Filter Check	Yes
24-Hour On/Off Timer	Yes
Clean Air Ionizer	
Remote Control	Full-Function
	i dii i diictioni
Air CFM (High/Med/Low)	241/224/206
Air CFM (High/Med/Low) Air Direction Control	
	241/224/206
Air Direction Control	241/224/206 Swing
Air Direction Control Fresh Air/Exhaust Vent/Closed	241/224/206 Swing No/Yes/No

Shipping Weight (Approx.) Warranty 5 year sealed system/1 year full parts and labor.

ASHRAE, D.O.E.

R410a

62 l bs



Performance

SPECIFICATIONS Refrigerant

#### PRODUCT DIMENSIONS

A-Height	27-29/32"
B-Width	18-24/32"
C-Depth	15-5/32"

